

WOLF OE LEVELTECH 5W-30 MS-SFE

01/06/2026
75648

A low SAPS ACEA C3 passenger car engine oil focused on the most recent Stellantis specification FPW9.55535/03 and on the PSA specifications B71 2290 and B71 2297 (for hot climates). Also suitable for diesel and gasoline engines from other car manufacturers which require an ACEA C3 SAE 5W-30 oil.

APPLICATIONS

Developed for a wide range of passenger cars, SUVs and light vans. It is designed for modern high efficiency gasoline, diesel and hybrid cars from Stellantis (PSA, Opel, Vauxhall), MB and GM, as well as for Asian vehicles that specifically require a SAE 5W-30 oil specification.

FEATURES

Aftertreatment protection: full aftertreatment device protection.

Cold start: excellent fluidity at low temperature.

Fuel economy: superior fuel economy and CO2 reduction.

SPECIFICATIONS

ACEA	C3	MB	229.51
API	SN Plus	MB	229.52
API	SP	OPEL	OV 040 1547 - D30
API	SQ	OPEL	OV 040 1547 - G30
CHINESE STANDARD	GB 11121	PSA	B71 2290
GM	dexos 2	PSA	B71 2297
MB	229.31	STELLANTIS	FPW9.55535/03

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	70.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.0
Viscosity index	ASTM D2270		168
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	9.9
Pour point	ASTM D6892	°C	-36
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com

