

WOLF S.T.O.U. 15W40

05/06/2026
1436

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.

APPLICATIONS

This oil is intended for the lubrication of gear boxes, differentials, final drives, power take-off, wet brakes and hydraulic systems of agricultural tractors and engines off-highway equipment.

FEATURES

Anti-wear and oxidation stability: proven protection of critical parts

SPECIFICATIONS

ACEA	E3	ZF	TE-ML 07D
AFNOR	NF E 68-603 E		
API	CG-4		
API	GL-4		
API	GL-5 (Low speed/high torque)		
API	SF/CE		
DIN	51524 T3 HVLPD		
ALLISON	C4 (Agriculture applic.)		
CASE	MAT 3525		
CASE	MAT 3526		
EATON VICKERS	I-280-S		
EATON VICKERS	M-2950-S		
FORD	ESN-M2C134 C/D		
FORD	ESN-M2C159 B/C		
FORD	FNH 82009203		
JD	J20C		
JD	J27		
MAN	271		
MB	227.1		
MF	M 1135		
MF	M 1139		
MF	M 1143		
MF	M 1144		
MF	M 1145		
NH	NH 024C		
Sauer Sunstrand/Danfoss	Hydro Static Trans Fluid		
ZF	TE-ML 03A		
ZF	TE-ML 05K		
ZF	TE-ML 06A		
ZF	TE-ML 06B		
ZF	TE-ML 06C		
ZF	TE-ML 07B		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.876
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	103
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.3
Viscosity index	ASTM D2270		142
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	10.7
Pour point	ASTM D6892	°C	-33
CCS viscosity at -20°C	ASTM D5293	mPa.s	5600
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

