

# WOLF ESSENTIAL SN/CF C3 5W40 PI

14/04/2025  
75608

This full synthetic engine oil meets the core requirements of ACEA and API for passenger cars. It keeps soot particles dispersed and prevents the formation of piston deposits.

## APPLICATIONS

This engine oil is recommended for direct injection diesel engines, including common rail direct fuel injection systems with or without aftertreatment system.

## FEATURES

Aftertreatment protection: full aftertreatment system protection.  
Total engine protection: outstanding engine cleanliness and durability.

## SPECIFICATIONS

ACEA	C3	MB	229.51
API	SN/CF	VW	505 00
MB	229.31	VW	505 01

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	80.5
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	13.8
Viscosity index	ASTM D2270		177
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	6.8
Pour point	ASTM D6892	°C	-42

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

