

# WOLF OFFICIALTECH OW-30 MS-BFE

27/02/2026  
65660

This is an ACEA C2/C3 engine oil based on carefully selected very high quality base oils. This oil is specifically formulated to meet the BMW Longlife-19 FE engine oil specification.

It is adapted to meet the requirements of the latest technology, highly engineered turbo engines requiring high performance and lower viscosity oils.

## APPLICATIONS

This ACEA C2/C3 and API SP engine oil is tailor made for the BMW Longlife-19 FE engine oil specification. It provides a multi vehicle application through the ACEA C2 specification. Optimum formulation for today's cars with exceptional film strength preventing oil film breakdown and reducing friction providing fuel economy and reliability.

## FEATURES

Cold start: excellent fluidity at low temperature.

Fuel economy: superior fuel economy and CO2 reduction.

Total engine protection: performance in keeping the engine clean.

## SPECIFICATIONS

ACEA	C2	MB	226.5
ACEA	C3	MB	229.31
API	SP	MB	229.51
BMW	LONGLIFE-04	OPEL	OV 040 1547 - D30
BMW	LONGLIFE-12FE	OPEL	OV 040 1547 - G30
BMW	LONGLIFE-19 FE	RENAULT	RN 0700
FIAT	9.55535-DS1	RENAULT	RN 0710
FIAT	9.55535-GS1		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.8421
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	66.63
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	12.10
Viscosity index	ASTM D2270		181
Pour point	ASTM D6892	°C	-9
Sulfated Ash	ASTM D874	Mass %	0.8
Flash Point COC	ASTM D92	°C	230
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	9.1

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

