

CHAMPION OEM SPECIFIC DCT FLUID

This is a lubricant based on carefully selected very high quality base oils, specifically developed for the dual clutch transmissions (DCT) of modern passenger cars. It ensures trouble-free operation of these gearboxes.

APPLICATIONS

Mainly intended for the DCT of VAG, this fluid can also be used for other 6-speed DCT transmissions, such as Chrysler Powershift, Ford Powershift, Mitsubishi TC-SST, Volvo Powershift, BMW Drivelogic 7-speed, etc.

FEATURES

Anti-wear protection: significantly extended transmission life

Extended oil life: excellent thermal and oxidation stability

Frictional properties: very smooth gear shifting, no vibration

SPECIFICATIONS

API	GL-4	CHRYSLER	68044345GA
BORGWARNER	WET DCT	CHRYSLER	Powershift 6 speed
BENTLEY	G 052 524-B2	DTR	13C130
BMW	6 speed DCT	FERRARI	7 Speed [Getrag]
BMW	83 22 2 446 673	FERRARI	TF DCT-F3
BMW	83 22 5 A53 CB2	FIAT	9.55550-DA11
BMW	83220306816	FIAT	9.55550-HE2
BMW	83220397244	FIAT	9.55550-MZ2
BMW	83220440214	FIAT	9.55550-MZ6
BMW	83222147477	FORD	1 490 761
BMW	83222148578	FORD	1 490 763
BMW	83222148579	FORD	F-DC
BMW	83222167666	FORD	MU7J 19A509 AA
BMW	83222409710	FORD	WSS-M2C200-D2
BMW	83222433157	FORD	WSS-M2C200-D3
BMW	83225B3AC81	FORD	WSS-M2C200-E1
BMW	DCTF-1	FORD	WSS-M2C218-A1
BMW	DCTF-1+	FORD	WSS-M2C936-A
BMW	DCTF-2	GM	DEXRON DCT
BMW	Drivelogic 7 speed	GM	FFL-4
BMW	DTF 1	GREAT WALL	GW7DCT1
BMW	FFL-4	GREAT WALL	GWM 7DCT450
BMW	MTF LT-3	HONDA	MTF III
BMW	MTF LT-5	HONDA	TYPE 2
BUGATTI	VEYRON (wet DCT)	HYUNDAI	04300-2N100
BYD	6DT35	HYUNDAI	04300-2N110 WDHO-1
BYD	QVBYD-A1909.0058.2013	KIA	04300-2N100
CHANGAN	DCTF	KIA	04300-2N110 WDHO-1
CHERY	730DHB/DHC 7DCT300	KUNLUN	DCTF-7S
CHERY	738DHA 7DCT380	MB	000 989 20 02
CHERY	9009011085	MB	000 989 61 04
CHRYSLER	68044345EA	MB	001 989 85 03

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com



MB	001 989 86 03	RENAULT	DW6
MB	002 989 04 03	RENAULT	EDC
MB	236.21	SINOPEC	DCTF-GS
MB	236.22	STELLANTIS	16 934 837 80
MB	236.24	SUZUKI	99000-22B27-036
MB	236.25	TOYOTA	0888581001
MB	239.21	TOYOTA	JWS 2271
MB	239.22	TOYOTA	LF
MB	SLS A0019898603	TOYOTA	LV 75W MT
MCLAREN	FFL-4	VOLVO	1161520-7
MITSUBISHI	DIAMOND QUEEN SSTF-1	VOLVO	1161838
MITSUBISHI	MZ320065	VOLVO	1161839
NISSAN	999MP-6TRT00P	VOLVO	32240415
NISSAN	DCT FLUID	VOLVO	32240419
NISSAN	GR6	VOLVO	B0T341 #1161838
NISSAN	GT-R R35	VOLVO	D1
NISSAN	LV MT-1	VOLVO	D2
NISSAN	R35 SPECIAL	VW	G 052 171
PKD	DCT Transmission Oil for ZF	VW	G 052 178
PORSCHE	000.043.20	VW	G 052 182
PORSCHE	000.043.207.29	VW	G 052 512
PORSCHE	000.043.207.30	VW	G 052 513
PORSCHE	000.043.210.44	VW	G 052 524
PORSCHE	000.043.305.63	VW	G 052 527
PORSCHE	971.094.307.02A	VW	G 052 529
PORSCHE	999.917.080.00	VW	G 052 536
PORSCHE	999.917.080.01	VW	G 052 726
PORSCHE	999.917.546.00	VW	G 052 798
PORSCHE	TF 0870	VW	G 055 512
PSA	1618078480	VW	G 055 524
PSA	9730 A8	VW	G 055 529
PSA	9734 S2	VW	G 055 536
PSA	JWS 2271	VW	G 055 549
PUNCH	DT2	VW	G 060 726
RENAULT	7711579456	VW	G 070 726
RENAULT	7711785243	VW	G009317
RENAULT	B0T450 EDC 6-Speed	VW	TL 521 82
RENAULT	DC4	ZF	0671090545
RENAULT	DW5	ZF	TE-ML 11

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.853
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	35.7
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.26
Viscosity index	ASTM D2270		173
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	202

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

