

RADIATOR COOLANT 50/50

14/04/2025
5069

This is an anti-freeze solution, based on mono-ethylene glycol and anti-corrosion additives in demineralised water. It contains no nitrites, amines or phosphates and gives excellent protection against corrosion without deposit formation. Easy to apply, the solution is already prepared.

APPLICATIONS

This liquid can be used in cooling circuits of the open or closed type with a protection against freezing until -36°C. Can be used during the whole year.

FEATURES

Anti-corrosion properties: complete system protection

Easy to use: ready-mixed

SPECIFICATIONS

<i>ASTM</i>	D3306	<i>FIAT</i>	55523/1
<i>ASTM</i>	D4985	<i>FORD</i>	SSM-97B9102A
<i>BS</i>	6580-1992	<i>GME</i>	13368
<i>SAE</i>	J1034	<i>MAN</i>	324
<i>BMW</i>	N600.69.0	<i>SCANIA</i>	S28917.3
<i>DAVID BROWN</i>	DBL-7700	<i>VW</i>	TL-VW774

TYPICAL CHARACTERISTICS

<i>Test</i>	<i>Method</i>	<i>Unit</i>	<i>Average results</i>
<i>pH</i>	<i>ASTM D1287</i>		<i>7.7</i>
<i>Density at 20°C</i>	<i>ASTM D4052</i>	<i>g/ml</i>	<i>1.073</i>
<i>Colour</i>	<i>VISUAL</i>		<i>Blue</i>
<i>Freezing point (refracto)</i>	<i>ASTM D3321</i>	<i>°C</i>	<i>-36</i>
<i>Water content</i>	<i>ASTM D1123</i>	<i>% wt/wt</i>	<i>50.0</i>

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfoil.com

WOLFOIL
CORPORATION