

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : GEAR OIL GL 5 LS SAE 75W90
Product code : 2410
Type of product : WOC
Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use
Industrial/Professional use spec : Non-dispersive use
Used in closed systems
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

WOLF OIL CORPORATION N.V.
Georges Gilliotstraat, 52
2620 Hemiksem, Antwerpen
België
T 0032 (0)3 870 00 00, F 0032 (0)3 870 00 99
msds@wolfoil.com

1.4. Emergency telephone number

Emergency number : 0032 (0)3 870 00 00

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Israel	Israel Poison Information Center Rambam Health Care Campus	6 Ha'Aliya Street 31096	+972 4 854 1900	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090	+356 2545 6508	
Sweden	Giftinformationscentralen	Box 60 500 171 76 Stockholm	112 – begär Giftinformation +46 10 456 6700 (Från utlandet)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment – Chronic Hazard, H412
Category 3

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP)	: -
Hazard statements (CLP)	: H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P273 - Avoid release to the environment. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH208 - Contains Methyl methacrylate. May produce an allergic reaction.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : The mineral oils in the product contain < 3% DMSO extract (IP 346)

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Polysulphides, di-tert-Bu	CAS-No.: 68937-96-2 EC-No.: 273-103-3 REACH-no: 01-2119540515-43	1 – 4.5	Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Phosphoric acid ester amine salt	EC-No.: 931-384-6 REACH-no: 01-2119493620-38	0.1 – 0.9	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Methyl methacrylate	CAS-No.: 80-62-6 EC-No.: 201-297-1 EC Index-No.: 607-035-00-6	0.1 – 0.24	Flam. Liq. 2, H225 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317
(Z)-N-octadecenylpropane-1,3-diamine	CAS-No.: 7173-62-8 EC-No.: 230-528-9 REACH-no: 01-2119487002-46	0.1 – 0.15	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT RE 1, H372 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	CAS-No.: 1213789-63-9 EC-No.: 627-034-4 REACH-no: 01-2119473797-19	0.1 – 0.15	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Polysulphides, di-tert-Bu	CAS-No.: 68937-96-2 EC-No.: 273-103-3 REACH-no: 01-2119540515-43	(46 ≤ C < 100) Skin Sens. 1B, H317
Phosphoric acid ester amine salt	EC-No.: 931-384-6 REACH-no: 01-2119493620-38	(9.39 ≤ C < 100) Skin Sens. 1, H317 (50.01 ≤ C < 100) Eye Irrit. 2, H319
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	CAS-No.: 1213789-63-9 EC-No.: 627-034-4 REACH-no: 01-2119473797-19	(10 ≤ C < 100) STOT RE 2, H373

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Not expected to require first aid measures.
First-aid measures after skin contact	: Wash skin with mild soap and water.
First-aid measures after eye contact	: In case of eye contact, immediately rinse with clean water for 10-15 minutes.
First-aid measures after ingestion	: Do not induce vomiting. Rinse mouth. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water fog. Foam. Powder. Dry chemical product.
Unsuitable extinguishing media	: Do not use a heavy water stream.

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Precautionary measures fire	: Exercise caution when fighting any chemical fire.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Impound and recover large spill by mixing it with inert granular solids.
Methods for cleaning up	: Detergent. Take up liquid spill into absorbent material sand, saw dust, kieselguhr.
Other information	: Spill area may be slippery. Use suitable disposal containers.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.
Handling temperature	: < 40 °C
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage temperature	: ≤ 40 °C
Storage area	: Store in dry, cool, well-ventilated area.

Germany

Storage class (LGK, TRGS 510)	: LGK 10-13 - Other combustible and non-combustible substances
-------------------------------	--

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

GEAR OIL GL 5 LS SAE 75W90	
Belgium - Occupational Exposure Limits	
Local name	Huiles minérales (brouillards) # Olie (minerale-; nevel)
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 02/09/2018
Methyl methacrylate (80-62-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Methyl methacrylate
IOEL TWA	50 ppm @8h
IOEL STEL	100 ppm @15min
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	208 mg/m ³ @8h
	50 ppm @8h
MAK (OEL STEL)	416 mg/m ³ @15min
	100 ppm @15min
Belgium - Occupational Exposure Limits	
Local name	Méthacrylate de méthyle # Methylmethacrylaat
OEL TWA	208 mg/m ³ @8h
	50 ppm @8h
OEL STEL	416 mg/m ³ @15min
	100 ppm @15min
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
OEL TWA	50 ppm @8h
OEL STEL	100 ppm @15min
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	50 ppm @8h
KGVI (OEL STEL)	100 ppm @15min
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	50 mg/m ³ @8h
	12 ppm @8h
NPK-P (OEL C)	150 mg/m ³ @15min
	36 ppm @15min
Denmark - Occupational Exposure Limits	
OEL TWA	102 mg/m ³ @8h
	25 ppm @8h

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methyl methacrylate (80-62-6)	
Estonia - Occupational Exposure Limits	
OEL TWA	50 ppm @8h
OEL STEL	100 ppm @15min
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	42 mg/m ³ @8h
	10 ppm @8h
HTP (OEL STEL)	210 mg/m ³ @15min
	50 ppm @15min
France - Occupational Exposure Limits	
VME (OEL TWA)	205 mg/m ³ @8h
	50 ppm @8h
VLE (OEL C/STEL)	410 mg/m ³ @15min
	100 ppm @15min
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	210 mg/m ³ @8h
	50 ppm @8h
Greece - Occupational Exposure Limits	
OEL TWA	50 ppm @8h
OEL STEL	100 ppm @15min
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	208 mg/m ³ @8h
Ireland - Occupational Exposure Limits	
OEL TWA	50 ppm @8h
OEL STEL	100 ppm @15min
Italy - Occupational Exposure Limits	
OEL TWA	50 ppm @8h
OEL STEL	100 ppm @15min
Latvia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ @8h
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	208 mg/m ³ @8h
	50 ppm @8h
TPRV (OEL STEL)	416 mg/m ³ @15min
	100 ppm @15min
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	205 mg/m ³
TGG-15min (OEL STEL)	410 mg/m ³

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methyl methacrylate (80-62-6)	
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m ³ @8h
NDSP (OEL C)	300 mg/m ³ @15min
Portugal - Occupational Exposure Limits	
OEL TWA	50 ppm @8h
OEL STEL	100 ppm @15min
Romania - Occupational Exposure Limits	
OEL TWA	205 mg/m ³ @8h
	50 ppm @8h
OEL STEL	410 mg/m ³ @15min
	100 ppm @15min
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	50 ppm @8h
NPHV (OEL STEL)	100 ppm @15min
Slovenia - Occupational Exposure Limits	
OEL TWA	210 mg/m ³ @8h
	50 ppm @8h
OEL STEL	420 mg/m ³ @15min
	100 ppm @15min
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	50 ppm @8h
VLA-EC (OEL STEL)	100 ppm @15min
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	210 mg/m ³ @8h
	50 ppm @8h
KTV (OEL STEL)	420 mg/m ³ @15min
	100 ppm @15min
Iceland - Occupational Exposure Limits	
OEL TWA	50 ppm @8h
OEL STEL	100 ppm @15min
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	100 mg/m ³ @8h
	25 ppm @8h
Korttidsverdi (OEL STEL)	400 mg/m ³ @15min
	100 ppm @15min

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Safety glasses. Gloves.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

No additional information available

8.2.2.2. Skin protection

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Hand protection:

Permeation time: minimum >480min long term exposure; material / thickness [mm]: >0,35 mm. Nitrile rubber (NBR) /

8.2.2.3. Respiratory protection

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Appearance	: Oily liquid.
Odour	: Characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 180 °C (ASTM D92)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 86 mm ² /s @ 40°C (ASTM D445)

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Solubility	: Slightly soluble, the product remains on the water surface.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 873 kg/m ³ @15°C (ASTM D4052)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

Strong oxidizers. acids. Bases.

10.6. Hazardous decomposition products

None under normal conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

(Z)-N-octadecenylpropane-1,3-diamine (7173-62-8)

LD50 oral rat	500 mg/kg (OECD 423)
---------------	----------------------

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

LD50 oral rat	1689 mg/kg OECD 401 - read across
---------------	-----------------------------------

Methyl methacrylate (80-62-6)

LD50 oral rat	7900 mg/kg
LD50 dermal rabbit	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat (Vapours)	29.8 mg/l/4h

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified

Methyl methacrylate (80-62-6)

Skin sensitization, - Skin contact, mouse	Skin sensitization (OECD 429)
---	-------------------------------

Germ cell mutagenicity : Not classified

Methyl methacrylate (80-62-6)

In vitro Mammalian Cell Gene Mutation Test, In vitro, mammalian	Positive (OECD 476, WOE does not support classification)
---	--

In vitro Mammalian Chromosomal Aberration Test, In vitro, mammalian	Equivocal (OECD 473, WOE does not support classification)
---	---

Rodent Dominant Lethal Test, In vivo, mammalian	Negative (OECD 478)
---	---------------------

Bacterial Reverse Mutation Test, In vitro, Bacteria	Negative (OECD 471)
---	---------------------

Carcinogenicity : Not classified

Methyl methacrylate (80-62-6)

Combined Chronic Toxicity/Carcinogenicity Studies, NOAEL, Inhalation, rat	Negative (104w; 5d/w, OECD 453)
---	---------------------------------

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

Methyl methacrylate (80-62-6)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified

Phosphoric acid ester amine salt

NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day @28d (OECD 407)
----------------------------	--

(Z)-N-octadecenylpropane-1,3-diamine (7173-62-8)

NOAEL (subacute, oral, 28 days)	1.25 mg/kg bodyweight/day (OECD 407)
---------------------------------	--------------------------------------

NOAEL (subchronic, oral, 90 days)	0.4 mg/kg bodyweight/day (OECD 408)
-----------------------------------	-------------------------------------

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard : Not classified

GEAR OIL GL 5 LS SAE 75W90

Viscosity, kinematic	86 mm²/s @ 40°C (ASTM D445)
----------------------	-----------------------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Polysulphides, di-tert-Bu (68937-96-2)	
EC50 - Crustacea [1]	63 mg/l @2d (Daphnia magna)
EC50 - Other aquatic organisms [1]	> 10000 mg/l @0,1d (Sludge)
EC50 72h - Algae [2]	> 100 mg/l @3d
Phosphoric acid ester amine salt	
LC50 - Fish [1]	24 mg/l Oncorhynchus mykiss
LC50 - Fish [2]	8.5 mg/l Pimephales promelas
EC50 - Crustacea [1]	91.4 mg/l 2d (Daphnia magna)
EC50 - Crustacea [2]	0.66 mg/l 21d (Daphnia magna)
EC50 96h - Algae [1]	6.4 mg/l @4d (Selenastrum capricornutum)
NOEC (chronic)	3.2 mg/l Oncorhynchus mykiss @4d
NOEC chronic crustacea	0.12 mg/l @21d (Daphnia magna)
NOEC chronic algae	1.7 mg/l @4d (Selenastrum capricornutum)
(Z)-N-octadecenylpropane-1,3-diamine (7173-62-8)	
LC50 - Fish [1]	> 0.1 mg/l (Brachydanio rerio)
EC50 - Crustacea [1]	> 0.01 mg/l (Daphnia magna)
EC50 72h - Algae [1]	0.507 mg/l (Desmodesmus subspicatus)
NOEC chronic crustacea	> 0.001 mg/l @21d (Daphnia magna)
NOEC chronic algae	0.188 mg/l (Desmodesmus subspicatus)
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	
LC50 - Fish [1]	0.11 mg/l (Pimephales promelas)
LC50 - Fish [2]	1.3 mg/l (Oncorhynchus mykiss)
LC50 - Other aquatic organisms [1]	0.9 mg/l (Cyprinodon variegatus)
EC50 - Crustacea [1]	0.011 mg/l @2d (Daphnia Magna)
EC50 - Crustacea [2]	0.27 mg/l @21d (Daphnia Magna)
EC50 72h - Algae [1]	> 0.13 mg/l (Desmodesmus subspicatus)
NOEC chronic crustacea	0.013 mg/l @21d (Daphnia magna)
NOEC chronic algae	0.01 mg/l @3d
Methyl methacrylate (80-62-6)	
LC50 - Fish [1]	> 79 mg/l @96h; Oncorhynchus mykiss
EC50 - Crustacea [1]	69 mg/l @48h; Daphnia magna
EC50 72h - Algae [1]	> 110 mg/l @72h; Pseudokirchneriella subcapitata
NOEC chronic fish	9.4 mg/l @35d; Danio rerio (OECD 210)
NOEC chronic crustacea	37 mg/l @21d; Daphnia magna (OECD 211)
NOEC chronic algae	110 mg/l @72h, Selenastrum capricornutum (OECD 201)

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.2. Persistence and degradability

GEAR OIL GL 5 LS SAE 75W90

Persistence and degradability	Not soluble in water, so only minimally biodegradable.
-------------------------------	--

Polysulphides, di-tert-Bu (68937-96-2)

Persistence and degradability	Rapidly degradable
Biodegradation	13 % % @OECD TG @28d

Phosphoric acid ester amine salt

Persistence and degradability	Rapidly degradable
BOD (% of ThOD)	3.6 % ThOD @28d (inherent sediment)
Biodegradation	7.4 % @28d (OECD TG 301B)

(Z)-N-octadecenylpropane-1,3-diamine (7173-62-8)

Persistence and degradability	Rapidly degradable
Biodegradation	66 % @28d (OECD 301D)

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

Persistence and degradability	Readily biodegradable.
Biodegradation	66 % @28d (OECD TG 301 B)

Methyl methacrylate (80-62-6)

Persistence and degradability	Rapidly degradable
Biodegradation	94 % @14d (OECD 301 C)

12.3. Bioaccumulative potential

Polysulphides, di-tert-Bu (68937-96-2)

Partition coefficient n-octanol/water (Log Kow)	6
---	---

(Z)-N-octadecenylpropane-1,3-diamine (7173-62-8)

Bioconcentration factor (BCF REACH)	0.5
Partition coefficient n-octanol/water (Log Pow)	0.03

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

Bioconcentration factor (BCF REACH)	> 500
Partition coefficient n-octanol/water (Log Kow)	> 4.33 @25 °C

Methyl methacrylate (80-62-6)

Partition coefficient n-octanol/water (Log Kow)	1.38
---	------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Additional information : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

14.3. Transport hazard class(es)

ADR
Transport hazard class(es) (ADR) : Not applicable

IMDG
Transport hazard class(es) (IMDG) : Not applicable

IATA
Transport hazard class(es) (IATA) : Not applicable

ADN
Transport hazard class(es) (ADN) : Not applicable

RID
Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

14.5. Environmental hazards

Other information : No supplementary information available

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 82	Conditions caused by methyl methacrylate

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
List of sensitizing substances (TRGS 907) : Contains sensitizing substances according TRGS 907.
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Polysulphides, di-tert-Bu is listed
SZW-lijst van mutagene stoffen : Polysulphides, di-tert-Bu is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Norway

Declaration number : 653424

Sweden

Swedish product registration number : 681135-0

15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	
2.2	EUH-statements	Added	
3.2	Composition/information on ingredients	Modified	
9.1	Viscosity, kinematic	Modified	
9.1	Density	Modified	
9.1	Flash point	Modified	
12.6	Adverse effects on the environment caused by endocrine disrupting properties	Added	

Abbreviations and acronyms:

	ACGIH: American Conference of Governmental Industrial Hygienists
	TWA: Time Weighted Average
	TLV: Threshold Limit Value
	ASTM: American Society for Testing and Materials
	ADR: Accord Européen Relatif au Transport International des Marchandises Dangereuses par Route
	RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
	ADNR: Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
	IMDG: International Maritime Dangerous Goods

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

	ICAO: International Civil Aviation Organization
	IATA: International Air Transport Association
	STEL: Short Term Exposure Limit
	LD50: median Lethal Dose for 50% of subjects
	ATE: acute toxicity estimate
	LC50: median Lethal Concentration for 50% of subjects
	EC50: concentration producing 50% effect

Other information

: The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains Methyl methacrylate. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

GEAR OIL GL 5 LS SAE 75W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.