

CHAMPION PRORACING GP 4T 5W40 ESTER +

This full synthetic engine oil suits the needs of the most demanding four-stroke motorcycles. Its Ester+ Adaptive Shield Technology surpasses the limits of conventional ester full synthetic products. This innovative formulation offers outstanding lubricating properties, including fuel economy and reduced wear, which directly improve protection and reduce engine friction. Its outstanding fluidity at low temperatures guarantees complete protection immediately after starting the engine.

APPLICATIONS

This motorcycle engine oil exceeds the standards of API SN, SM, SL, SJ, SH and SG; extending its applicability to a wide range of four-stroke motorcycles. It is perfectly suited for the engines, transmissions and wet clutches of these motorcycles. This lubricant is formulated to provide the highest protection level under the most extreme conditions.

FEATURES

Champion Ester+ Adaptive Shield Technology: increased engine, transmission & wet clutch performance

SPECIFICATIONS

API

SN

JASO

approval MA2

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	81
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.6
Viscosity index	ASTM D2270		172
B.N. [HCL04 method]	ASTM D2896	mg KOH/g	7.3
Pour point	ASTM D6892	°C	-42
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

