

# CHAMPION OEM SPECIFIC MULTI VEHICLE ATF HD-ND

This automatic transmission fluid is an high performance heavy duty synthetic transmission fluid. It is designed to deliver normal drain capabilities up to 60 000 km. It contains high quality synthetic base oils and an advanced additive technology. It is suitable for use in automatic transmission systems in both heavy duty trucks and buses.

## APPLICATIONS

This automatic transmission fluid is designed for extended drain intervals for heavy duty trucks and buses as well as off-road equipment.

## FEATURES

Frictional properties: smooth shift performance.

Extended oil life: excellent thermal and oxidation stability.

Anti-wear protection: extended transmission life.

## SPECIFICATIONS

<b>ALLISON</b>	C4	<b>VOITH</b>	approval H55.6336xx
<b>ALLISON</b>	TES 295	<b>VOITH</b>	H55.6335xx
<b>DTFR</b>	13C170	<b>VOLVO</b>	STD 1273,40 [97340]
<b>FORD</b>	MERCON	<b>VOLVO</b>	STD 1273,41 [97341]
<b>GM</b>	DEXRON III-H	<b>ZF</b>	TE-ML 03D
<b>MAN</b>	339 L1	<b>ZF</b>	TE-ML 04D
<b>MAN</b>	339 V1/Z1	<b>ZF</b>	TE-ML 14A
<b>MAN</b>	339 V2/Z2	<b>ZF</b>	TE-ML 14B
<b>MAN</b>	339 Z11	<b>ZF</b>	TE-ML 14C
<b>MAN</b>	339 Z3	<b>ZF</b>	TE-ML 16L
<b>MB</b>	236.9	<b>ZF</b>	TE-ML 17C
<b>MB</b>	236.93	<b>ZF</b>	TE-ML 20B

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	42.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	8.4
Viscosity index	ASTM D2270		181
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	18000
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

