

MULTIGRADE SN/CF SAE 5W40

02/09/2025
24116

This is a full synthetic lubricant based on carefully selected very high quality base oils and high quality additives of the latest generation, specially designed to meet the strict requirements of manufacturers. This provides an excellent fluidity at low temperatures, a very low resistance when starting, an exceptional viscosity index and a very high thermal stability.

APPLICATIONS

This oil is used in gasoline engines of cars, which demand the highest performance and diesel engines of passenger cars with turbo and direct fuel injection. The high quality allows extended drain intervals, according to the specific requirements of manufacturers.

FEATURES

Total engine protection: performance in keeping the engine clean

Cold start: excellent fluidity at low temperature

Drain interval extension: longer oil drain interval

SPECIFICATIONS

ACEA	A3/B4	PORSCHE	A40
API	SN/CF	PSA	B71 2296
BMW	LONGLIFE-01	RENAULT	RN 0700
MB	226.5	RENAULT	RN 0710
MB	229.3	VW	502 00
OPEL	GM-LL-B-025	VW	505 00

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.853
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	80.7
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.6
Viscosity index	ASTM D2270		172
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	10.4
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	6100
Sulfated Ash	ASTM D874	Mass %	1.2
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfoil.com

WOLFOIL
CORPORATION