

# ATF LIFE PROTECT 6

02/09/2025  
3012

*This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.*

## APPLICATIONS

Mainly intended for the ZF-6 speed automatic transmissions, as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid (e.g. Audi Quattro).

## FEATURES

Anti-wear protection: significantly extended transmission life

Frictional properties: very smooth gear shifting, no vibration

Extended oil life: excellent thermal and oxidation stability

## SPECIFICATIONS

<b>AML</b>	4G4319A509/AA/S	<b>HYUNDAI</b>	040000C90SG
<b>BENTLEY</b>	PY112995PA	<b>JAGUAR</b>	Fluid 8432
<b>BMW</b>	83 22 2 305 396	<b>LAND ROVER</b>	TYK500050
<b>BMW</b>	83220142516	<b>MASERATI</b>	231603
<b>BMW</b>	ATF 2	<b>VW</b>	G 055 005
<b>BMW</b>	M-1375.4	<b>ZF</b>	TE-ML 11

## TYPICAL CHARACTERISTICS

<b>Test</b>	<b>Method</b>	<b>Unit</b>	<b>Average results</b>
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	31.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.17
Viscosity index	ASTM D2270		152
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	202
Colour	VISUAL		AMBER

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfoil.com](http://www.wolfoil.com)

**WOLFOIL**  
CORPORATION