

CHAMPION ACTIVE DEFENCE

20W50 SF/CD

Multigrade engine oil for the lubrication of gasoline and diesel engines of passenger cars with natural aspiration or turbo charging. This oil is characterized by a combination of good detergent and good dispersion properties, together with a low ash content.

APPLICATIONS

This oil is suitable for the lubrication of gasoline and diesel engines, with or without turbo from 1980 to 1989.

FEATURES

Total engine protection: engine protection and cleanliness

SPECIFICATIONS

API	SF/CD	MB	226.1
MIL	L-46152 B		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.886
Kinematic viscosity at 40°C	ASTM D445	mm²/s	170
Kinematic viscosity at 100°C	ASTM D445	mm²/s	18.4
Viscosity index	ASTM D2270		121
B.N. [HCL04 method]	ASTM D2896	mg KOH/g	5.9
Pour point	ASTM D6892	°C	-36
CCS viscosity at -15°C	ASTM D5293	mPa.s	7800
Flash Point COC	ASTM D92	°C	240
Sulfated Ash	ASTM D874	Mass %	0.9

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

