

# CHAMPION OEM LEVEL 5W30 C4

This full synthetic engine oil is formulated to meet the specifications of different OEMs. The low SAPS formula guarantees complete DPF protection. Furthermore, its fluidity at low temperatures guarantee easy starting in winter conditions.

## APPLICATIONS

Can be used for gasoline and diesel engines of passenger cars, more specifically for Renault, requiring the ACEA C4 and RN 720 specifications.

## FEATURES

Aftertreatment protection: aftertreatment system compatible

Total engine protection: outstanding engine cleanliness and durability

## SPECIFICATIONS

<b>ACEA</b>	C3	<b>MB</b>	229.31
<b>ACEA</b>	C4	<b>MB</b>	229.51
<b>FIAT</b>	9.55535-S4	<b>RENAULT</b>	RN 0720
<b>MB</b>	226.51	<b>SUZUKI</b>	SFU

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	69.1
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	11.7
Viscosity index	ASTM D2270		165
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	7.2
Pour point	ASTM D6892	°C	-45
Sulfated Ash	ASTM D874	Mass %	0.5
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

