

WOLF EXTENDTECH 80W-90 GL 5

05/06/2026
2308

This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

APPLICATIONS

Recommended for all hypoid transmissions and also suitable for spiral bevel gears, worm wheels and most transaxles.

FEATURES

Frictional properties: easy gear shifting
Anti-wear protection: long transmission life

SPECIFICATIONS

API	GL-5	ZF	TE-ML 08
MIL	L-2105 C	ZF	TE-ML 12E
MIL	L-2105 D	ZF	TE-ML 16B
MAN	342 M-1	ZF	TE-ML 16C
MAN	342 M-2	ZF	TE-ML 17B
VOLVO	97305	ZF	TE-ML 19B
ZF	TE-ML 05A	ZF	TE-ML 21A
ZF	TE-ML 07A		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.8970
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	148.62
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	15.20
Viscosity index	ASTM D2270		103
Pour point	ASTM D6892	°C	-33
Brookfield viscosity at -26 C	ASTM D2983	mPa.s	120000
Flash Point COC	ASTM D92	°C	210

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

