

# WOLF AROW ISO 10

14/04/2025  
4001

A mineral oil, specifically designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

## ZASTOSOWANIA

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

## CECHY

Anti-wear and oxidation stability: superior protection

Anti-foam properties: excellent anti-foam properties

Temperature stability: adequate viscosity stability

## SPECYFIKACJA

|       |                |               |            |
|-------|----------------|---------------|------------|
| AFNOR | NF E 48-603 HM | ISO           | 6743-4, HM |
| AFNOR | NF E 48-690    | DENISON       | HF-2       |
| AFNOR | NF E 48-691    | EATON VICKERS | I-286-S    |
| DIN   | 51524 Part 2   | EATON VICKERS | M-2950-S   |
| ISO   | 11158, HM      |               |            |

## TYPOWE CECHY

| Test                                 | Metoda     | Jednostka          | Średni wynik |
|--------------------------------------|------------|--------------------|--------------|
| Gęstość w temp. 15°C                 | ASTM D4052 | g/ml               | 0.836        |
| Lepkość kinematyczna przy temp. 40°C | ASTM D445  | mm <sup>2</sup> /s | 10.8         |
| Lepkość kinematyczna w temp. 100°C   | ASTM D445  | mm <sup>2</sup> /s | 2.82         |
| Indeks lepkości                      | ASTM D2270 |                    | 119          |
| Temperatura krzepnięcia              | ASTM D6892 | °C                 | -33          |
| Tempera zapłonu metodą Clevelanda    | ASTM D92   | °C                 | 154          |

Zastrzegamy sobie prawo do modyfikowania ogólnych charakterystyk naszych produktów, aby umożliwić naszym klientom czerpanie maksymalnych korzyści z najnowszych odkryć techniki.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

