

# WOLF S.T.O.U. 15W30

14/04/2025  
1435

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agriculture tractors.

## APPLICATIONS

This multigrade oil is advised for the lubrication of charged and uncharged diesel engines, 4-stroke gasoline and LPG-engines. This oil is intended for the lubrication of gear boxes, differentials, final drives, power take-off, wet brakes and hydraulic systems of agricultural tractors and engines of off-highway equipment.

## FEATURES

Anti-wear and oxidation stability: proven protection of critical parts

## SPECIFICATIONS

ACEA	E3
AFNOR	NF E 68-603 E
API	CG-4
API	GL-4
API	GL-5 (Low speed/high torque)
API	SF/CE
DIN	51524 T3 HVL PD
ALLISON	C4 (Agriculture applic.)
CASE	MAT 3525
CASE	MAT 3526
EATON VICKERS	M-2950-S
FORD	ESN-M2C134 C/D
FORD	ESN-M2C159 B/C
FORD	FNH 82009202
JD	J20C
JD	J27
MF	M 1135
MF	M 1139
MF	M 1143
MF	M 1144
MF	M 1145
NH	NH 030C
ZF	TE-ML 03A
ZF	TE-ML 05K
ZF	TE-ML 06A
ZF	TE-ML 06B
ZF	TE-ML 06C
ZF	TE-ML 07B
ZF	TE-ML 07D

**WOLF OIL CORPORATION NV**

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.874
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	81.7
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	10.8
Viscosity index	ASTM D2270		118
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	10.7
Pour point	ASTM D6892	°C	-33
CCS viscosity at -20°C	ASTM D5293	mPa.s	6600
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

**WOLF OIL CORPORATION NV**

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

