

# CHAMPION **PRO RACING** TRANS/AXLE LS 75W-140 ESTER

This is a sustainable RRBO high performance gearbox and transaxle lubricant, enriched with ester and PAO, for racing vehicles offering an excellent anti-wear and EP protection, a better resistance at high temperatures and a longer oil life time.

## APPLICATIONS

This sustainable RRBO lubricant can be used in gearboxes, transaxles and differentials with or without limited slip of racing vehicles.

## FEATURES

Anti-wear protection: extended component life.

Extended oil life: excellent thermal and oxidation stability.

## SPECIFICATIONS

|                |                             |           |                               |
|----------------|-----------------------------|-----------|-------------------------------|
| API            | GL-5                        | MB        | 235.61                        |
| API            | GL-6                        | M-SPORT   | Rally3/Rally4/Rally5/R1/R2/R3 |
| API            | MT-1                        | NISSAN    | 2189E                         |
| DUTCHMAN AXLES | SFU                         | RICARDO   | SFU                           |
| MIL            | L-2105 B                    | SADEV     | SFU                           |
| MIL            | L-2105 C                    | SALISBURY | SFU                           |
| MIL            | L-2105 D                    | SCANIA    | STO 1:0                       |
| MIL            | L-2105 E                    | SCANIA    | STO 2:0A                      |
| SAE            | J 2360                      | VW        | G 052 539                     |
| ARVIN MERITOR  | 0-76-N                      | X-TRAC    | SFU                           |
| BMW            | 83 22 1 470 080             | ZF        | TE-ML 05A                     |
| BMW            | 83 22 2 282 583             | ZF        | TE-ML 05B                     |
| BMW            | 83 22 9 407 803             | ZF        | TE-ML 05C                     |
| BMW            | 83 22 9 407 870             | ZF        | TE-ML 05D                     |
| BMW            | MSP/A                       | ZF        | TE-ML 07A                     |
| CHRYSLER       | 68218658AA                  | ZF        | TE-ML 12D                     |
| CHRYSLER       | MS 8985                     | ZF        | TE-ML 12N                     |
| DANA           | SFU                         | ZF        | TE-ML 16F                     |
| DREXLER        | SFU                         | ZF        | TE-ML 16G                     |
| FERRARI        | PAKELO GLOBAL MULTIGEAR DLS | ZF        | TE-ML 19C                     |
| FORD           | ESW-M2C104-A                | ZF        | TE-ML 21A                     |
| FORD           | ESW-M2C119-A                | ZF        | TE-ML 21C                     |
| FORD           | WSS-M2C187-A                | ZF        | TE-ML 21D                     |
| GM             | 12346140                    |           |                               |
| GM             | 1942386                     |           |                               |
| GM             | 9986226                     |           |                               |
| GM             | 9986290                     |           |                               |
| HEWLAND        | SFU                         |           |                               |
| HOLLINGER      | SFU                         |           |                               |
| MACK           | GO-J                        |           |                               |

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)





## TYPICAL CHARACTERISTICS

| Test                         | Method     | Unit               | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C              | ASTM D4052 | g/ml               | 0.898           |
| Kinematic viscosity at 40°C  | ASTM D445  | mm <sup>2</sup> /s | 179             |
| Kinematic viscosity at 100°C | ASTM D445  | mm <sup>2</sup> /s | 24.3            |
| Viscosity index              | ASTM D2270 |                    | 167             |
| Pour point                   | ASTM D6892 | °C                 | -51             |
| Colour                       | VISUAL     |                    | LIGHT BROWN     |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

