

WOLF TRACTOFLUID 50

25/09/2026
3119

Full synthetic oil designed to deliver exceptional performance for wet brakes across a wide temperature range and under all operating conditions. It provides superior wear protection, reduces friction (hence lower fuel consumption), and minimizes brake noise.

APPLICATIONS

This oil is primarily intended for the Volvo "standard 97304 (WB 102)" applications. But can also be used for automatic transmissions, hydraulic systems, wet brakes, convertors for tractors, forklifts and different off-highway equipment providing the viscosity grade 75W80 is recommended.

FEATURES

Anti-wear and oxidation stability: reliable protection of all parts

SPECIFICATIONS

	GL-4	ZF	TE-ML 21F
API			
DIN	51524 T3 HVLPD		
AGCO/ALLIS	821 XL		
CASE	MAT 3505/3525/3526		
CASE	MAT 3540		
CASE	MS 1206/1207/1209		
CLAAS	RENAULT AGRICULTURE		
FORD	ESN-M2C134 D		
FORD	FNHA-2-C-201.00		
JD	J20 D		
KUBOTA	SUPER UDT ²		
KUBOTA	UDT		
MC CORMICK	HTX		
MF	M 1143		
MF	M 1145		
NH	NH 410B/C		
VALTRA	G2-08		
VALTRA	G2-B10		
VOLVO	97303/WB101		
VOLVO	97304/WB102		
VOLVO	STD 1273,03 (97303)		
ZF	TE-ML 03E		
ZF	TE-ML 05F		
ZF	TE-ML 06D		
ZF	TE-ML 06K		
ZF	TE-ML 06N		
ZF	TE-ML 06R		
ZF	TE-ML 17E		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.857
Kinematic viscosity at 40°C	ASTM D445	mm²/s	40.8
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.7
Viscosity index	ASTM D2270		161
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	7.4
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	23700

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

