

WOLF CENTRAL HYDRAULIC FLUID ASIAN

01/09/2026
5097

This central hydraulic fluid is based on carefully selected very high quality base oils and the latest additive technology for the optimum functioning of hydraulic systems.

It is reliable power transmission fluid, even under difficult conditions, with a high and stable viscosity index

APPLICATIONS

This CHF is especially developed for the performance requirements of hydraulic systems (power steering) of Asian manufacturers in a wide temperature range.

Compatible with many common elastomers and sealing materials.

FEATURES

Pour point: excellent low temperature properties.

SPECIFICATIONS

ACURA	08206-9002A	MITSUBISHI	DIAMOND SP III
HONDA	08206-9002A	MITSUBISHI	PS FLUID
HONDA	PSF-2	NISSAN	PSF-II
HONDA	PSF-S	PSA	9735 EJ
HONDA	PSF-V	SUBARU	K0209A0080
HYUNDAI	PSF-3	SUBARU	PS FLUID
KIA	PSF-III	TOYOTA	008886-01
MAZDA	PSF	TOYOTA	PSF-EH
MITSUBISHI	DIAMOND PSF-2M		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.870
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	36.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.5
Viscosity index	ASTM D2270		180
Pour point	ASTM D6892	°C	-52
Flash Point COC	ASTM D92	°C	186
Colour	VISUAL		YELLOW

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

