

WOLF OFFICIALTECH 10W40 S3

16/05/2025
1727

This is a semi synthetic lubricant based on carefully selected very high quality base oils. This "long-drain" oil is engineered to provide outstanding lubrication to modern, high performance diesel engines.

APPLICATIONS

This oil is suitable for Euro IV and Euro V engines. Due to the high ash content, this oil is not suitable for most engines and vehicles equipped with a particulate filter.

FEATURES

Emission compatibility: superior emission reduction

Total engine protection: outstanding engine cleanliness and durability

Cold start: very good fluidity at low temperature

SPECIFICATIONS

ACEA	E4	MB	235.28
ACEA	E7	MTU	Oil Category 1
API	CF-4	MTU	Oil Category 2
API	CG-4	MTU	Oil Category 3
API	CH-4	RENAULT	approval RLD-2
API	CI-4/SL	RENAULT	RLD
JASO	DH-1	RENAULT	RXD
ALLISON	C4	SCANIA	approval LDF-3
CATERPILLAR	ECF-1a	SCANIA	LDF-2
CATERPILLAR	ECF-2	VOITH	Retarder Oil Class A
CATERPILLAR	TO-2	VOITH	Retarder Oil Class B
CUMMINS	CES 20072	VOLVO	approval VDS-3
CUMMINS	CES 20076		
CUMMINS	CES 20077		
CUMMINS	CES 20078		
DAF	EXTENDED DRAIN		
DETROIT DIESEL	DFS 93K215		
DEUTZ	DQC-III-10		
DEUTZ	DQC-III-18		
DTFR	13D110		
DTFR	15B110		
DTFR	15B120		
GLOBAL	DHD-1		
IVECO	18-1804 Classe T2 E7		
IVECO	18-1804 Classe T3 E4		
MACK	approval EO-N		
MACK	EO-M PLUS		
MACK	EO-N Premium Plus		
MAN	M3275-1		
MAN	M3277		
MB	229.1		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.870
Kinematic viscosity at 40°C	ASTM D445	mm²/s	86.3
Kinematic viscosity at 100°C	ASTM D445	mm²/s	13.3
Viscosity index	ASTM D2270		155
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	16.1
Pour point	ASTM D6892	°C	-39
CCS viscosity at -25°C	ASTM D5293	mPa.s	6700
Sulfated Ash	ASTM D874	Mass %	1.9
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

