CHAMPION *LIFE EXTENSION* ATF DII

This is an oil with a high viscosity index for automatic transmissions. It is characterized by a high chemical stability, increased anti-wear properties and an excellent resistance against ageing.

APPLICATIONS

It can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron II-D requirements.

FEATURES

Anti-wear protection: long transmission life
Oil life durability: high level of thermal and oxidation stability

SPECIFICATIONS

ALLISON	C4	**MB**	236.7
CATERPILLAR	TO-2	**VOITH**	H55.6335xx
DTFR	approval 13C140	**ZF**	TE-ML 03D
FIAT	9.55550-AG1	**ZF**	TE-ML 04D
FORD	M2C-138CJ, Mercon	**ZF**	TE-ML 09
GM	6137-M DEXRON II-D	**ZF**	TE-ML 11A
MAN	339 V1/Z1	**ZF**	TE-ML 14A
MB	236.5	**ZF**	TE-ML 17C

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm²/s	37
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.4
Viscosity index	ASTM D2270		170
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	3
Pour point	ASTM D6892	°C	-39
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	45000
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 3 870 00 00
www.championlubes.com

The CHAMPION brand and design are registered trademarks of Champion Chemicals NV – Made in Belgium