The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OFFICIALTECH MULTI VEHICLE ATF HD-LD

This transmission fluid is an ultra high performance heavy duty synthetic transmission fluid. It is designed to deliver significantly extended drain capabilities. It contains superior quality synthetic base oils and advanced additive technologies and is suitable for use in automatic transmission systems in both heavy duty trucks and buses.

APPLICATIONS

This transmission fluid is designed for extended drain in heavy duty automatic truck and bus as well as offroad equipment transmissions.

FEATURES

Frictional properties: Very smooth gear shifting, no vibration Anti-wear protection: Significantly extended transmission life Extended oil life: Excellent thermal and oxidation stability

SPECIFICATIONS

DTFR	13C140	
DTFR	13C150	
DTFR	13C170	
FORD	WSS-M2C195-A	
GM	DEXRON III-G	
MAN	339 V1	
MAN	339 V2	
MAN	approval 339 Z12	
MAN	approval 339 Z3/V3	
MB	236.6	
MB	236.7	
MB	236.8	
MB	236.9	
VOITH	approval 150.014524.xx	
VOITH	H55.6335xx	
VOITH	H55.6336xx	
VOLVO	STD 1273,39 (97339)	
VOLVO	STD 1273,40 (97340)	
VOLVO	STD 1273,41 (97341)	
VOLVO	STD 1273,42 (97342)	
ZF	approval TE-ML 04D	
ZF	approval TE-ML 14C	
ZF	approval TE-ML 16M	
ZF	approval TE-ML 16S	
ZF	approval TE-ML 20C	
ZF	approval TE-ML 25C	
ZF	TE-ML 03D	

WOLF OIL CORPORATION NV





TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
lest	INIELIIUU	Ollit	Average results
Density at 15°C	ASTM D4052	g/ml	0.842
Kinematic viscosity at 40°C	ASTM D445	mm²/s	36.9
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.08
Viscosity index	ASTM D2270		157
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	13000
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

