

WOLF RACING TRANS/AXLE LS 75W-90 ESTER

12/05/2026
65522

This is a high performance gearbox and transaxle lubricant, enriched with ester and PAO, for racing vehicles offering an excellent anti-wear and EP protection, a better resistance at high temperatures and a longer oil life time.

APPLICATIONS

This transmission and axle oil can be used in gearboxes, transaxles, and differentials with or without limited slip of racing vehicles.

FEATURES

Anti-wear protection: extended component life.
Extended oil life: excellent thermal and oxidation stability.

SPECIFICATIONS

API	GL-5	HOLLINGER	SFU
API	MT-1	MACK	GO-J
DUTCHMAN AXLES	SFU	MB	235.61
MIL	L-2105 B	MCLAREN	MOB PTX
MIL	L-2105 C	M-SPORT	Rally3/Rally4/Rally5/R1/R2/R3
MIL	L-2105 D	NISSAN	2189E
MIL	L-2105 E	PORSCHE	999.917.067.00
SAE	J 2360	PORSCHE	999.917.090.00
ARVIN MERITOR	0-76-E	RICARDO	SFU
BMW	83 22 1 470 080	SADEV	SFU
BMW	83 22 2 282 583	SALISBURY	SFU
BMW	MSP/A	SCHMIDT	SFU
CHRYSLER	MS 9763	ANTRIEBSTECHNIK	
DANA	SFU	VW	G 052 539
DREXLER	SFU	VW	G 055 145
FERRARI	PAKELO GLOBAL MULTIGEAR DLS	X-TRAC	SFU
FORD	ESW-M2C104-A	ZF	TE-ML 05A
FORD	ESW-M2C119-A	ZF	TE-ML 05B
FORD	WSP-M2C197-A	ZF	TE-ML 05C
FORD	WSS-M2C942-A	ZF	TE-ML 05D
GM	1940058	ZF	TE-ML 07A
GM	88862624	ZF	TE-ML 12D
GM	88862625	ZF	TE-ML 12N
GM	93165388	ZF	TE-ML 16F
GM	9986226	ZF	TE-ML 16G
GM	9986290	ZF	TE-ML 19C
HEWLAND	SFU	ZF	TE-ML 21A

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.872
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	99.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	15.1
Viscosity index	ASTM D2270		160
Pour point	ASTM D6892	°C	-42
Colour	VISUAL		LIGHT BROWN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.