WOLF AROW
HV ISO 22

02/03/2026
4404

A high viscosity index paraffinic oil, based on selected ingredients, specifically intended for use in hydraulic circuits. Superior performance in keeping the system clean by reducing the formation of deposits. It also demonstrates good filterability, water separation , and quick air release.

KÄYTTÖKOHTEET

This oil is suitable for hydraulic systems, functioning at variable temperatures and high pressures. It can also be used in gear boxes, which require an oil with a high viscosity index and assuring mechanical and chemical stability. Applicable for regulation systems and hydraulic steering.

OMINAISUUDET

Anti-wear and oxidation stability: superior protection
Anti-foam properties: excellent anti-foam properties
Temperature stability: superior viscosity stability

LUOKITUKSET

AFNOR	NF E 48-603 HV	PARKER (DENISON)	HF-0, HF-1, HF-2
AFNOR	NF E 48-690	SAE	MS1004
AFNOR	NF E 48-691	SEB	181222
AGMA	9005-E02-RO	VICKERS	I-286-S3
AIST	126 (US Steel)	DENISON	HF-2
AIST	127 (US Steel)	DTFR	31B100
ASTM	D6158 HV	EATON VICKERS	I-286-S
DIN	51524 Part 3	EATON VICKERS	M-2950-S
ISO	11158, HV	EATON	E-FDGN-TB002-E
ISO	20763	EATON	M-2950-S (35VQ25 pump test)
ISO	6743-4, HV	GM	LS2 AW hyd.oil
JCMAS	HK P041	MB	341.0

TYYPILLISET OMINAISUUDET

Testi	Menetelmä	Yksikkö	Keskimääräinen tulos
Tiheys lämpötilassa 15 °C	ASTM D4052	g/ml	0.859
Kinemaattinen viskositeetti lämpötilassa 40 °C	ASTM D445	mm²/s	21.6
Kinemaattinen viskositeetti lämpötilassa 100 °C	ASTM D445	mm²/s	5
Viskositeetti-indeksi	ASTM D2270		168
Jähmepiste	ASTM D6892	°C	-39
Leimahduspiste (COC)	ASTM D92	°C	186

Pidätämme oikeuden muuttaa tuotteidemme yleisominaisuuksia, jotta asiakkaamme voivat hyödyntää uusimpia teknisiä uudistuksiamme.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV