

# CHAMPION AGRILINE 4T SAE 30 SJ

*This is an engine oil specifically designed for the lubrication of modern 4-stroke gasoline engines. The special composition ensures a perfect operation of the equipment and an excellent protection against dirt and deposits.*

## APPLICATIONS

*It is specifically formulated for the lubrication of the 4-stroke engines of garden and construction machines lawn mowers and auxiliary engines.*

## FEATURES

*Total engine protection: good engine protection and cleanliness*

## SPECIFICATIONS

API SJ/CD JASO MA

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.893
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	85.2
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	10.7
Viscosity index	ASTM D2270		108
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	7.0
Pour point	ASTM D6892	°C	-27
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

