

# WOLF ELECTRUM TRANS FLUID

14/04/2025  
65301

This is a full synthetic lubricant based on carefully selected very high quality base oils, especially formulated for automatic transmissions in electric cars (e-ATF) and hybrid cars. It provides excellent frictional durability and superior performance.

## APPLICATIONS

This ATF is specifically recommended for automatic transmissions in electric vehicles (e-ATF) and hybrid vehicles.

## FEATURES

Optimum electrical properties: allowing high voltages applications.

Frictional properties: very smooth gear shifting, no vibration.

Extended oil life: excellent thermal and oxidation stability.

## SPECIFICATIONS

TESLA EDF-2 (1616951-04-A)

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.845
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	31.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.2
Viscosity index	ASTM D2270		160
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	11800
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

