CHAMPION OEM SPECIFIC ATF MB FE

This is a full synthetic lubricant based on carefully selected very high quality base oils, intended for the latest MB 7-speed automatic transmissions from MB (NAG2FE+). It provides excellent frictional durability, superior performance and fuel economy.

APPLICATIONS

This product is recommended for sports vehicles (NAG2FE+) and is not backwards compatible with the previous 5- and 7- speed transmissions, which require MB 236.10, 236.12, 236.14.

FEATURES

Anti-wear protection: significantly extended transmission life Frictional properties: very smooth gear shifting, no vibration Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

INFINITI	MATIC-G	МВ	236.15
MAZDA	FZ	NISSAN	MATIC-G

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm²/s	20.9
Kinematic viscosity at 100°C	ASTM D445	mm²/s	4.79
Viscosity index	ASTM D2270		158
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	3500
Flash Point COC	ASTM D92	°C	178
Colour	VISUAL		DARK BLUE

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

