

WOLF VITALTECH MULTI VEHICLE ATF

14/04/2025
3010

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions, meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: significantly extended transmission life
Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

JASO	M315, Class 1A	FIAT	9.55550-AV1
AISIN-WARNER	JWS 3309	FIAT	9.55550-AV4
AISIN-WARNER	JWS 3314	FORD	MERCON
AISIN-WARNER	JWS 3317	FORD	MERCON V
ALFA ROMEO	HP20	FORD	WSS-M2C195-A
ALLISON	C4	FORD	WSS-M2C919-E
ALLISON	TES 295	FORD	WSS-M2C922-A1
ALLISON	TES 389	GM	DEXRON II-D
BMW	81 22 9 400 275	GM	DEXRON II-E
BMW	81 22 9 401 220	GM	DEXRON III-G
BMW	83 22 0 026 922	GM	DEXRON III-H
BMW	83 22 0 403 248	HONDA	ATF Z-1
BMW	83 22 0 403 249	HYUNDAI	ATF RED 1K
BMW	83 22 2 344 206	HYUNDAI	SP-II
BMW	83 22 2 355 599	HYUNDAI	SP-III
BMW	83 22 9 407 765	JAGUAR	JLM 20292 (LA 3403-M115)
BMW	ATF 4	JAGUAR	JLM 21044
BMW	ATF 6	LAND ROVER	LR002748
BMW	ETL 7045E	LAND ROVER	N402
BMW	ETL 8072B	MAZDA	ATF F-1
BMW	LA 2634	MAZDA	ATF M-V (Type M5)
BMW	LT 71141	MB	236.10
CHRYSLER	AS68RC ATF	MB	236.11
CHRYSLER	ATF +3 AND +4	MB	236.3
CHRYSLER	MS 9602	MB	236.5
DTFR	13C100	MB	236.6
DTFR	13C110	MB	236.7
DTFR	13C140	MB	236.8
DTFR	13C150	MB	236.9
DTFR	13C170	MB	236.91
DTFR	13C180	MINISUBISHI	4030401

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



mitsubishi	ATF J2	toyota	TYPE T-IV
mitsubishi	DIA QUEEN ATF-PA	VOLVO Constr. Equip. (VCE)	1273,41
mitsubishi	V5AWF	VOLVO	1161540
NISSAN	MATIC-D	VW	G 052 025
NISSAN	MATIC-J	VW	G 052 055
NISSAN	MATIC-K	VW	G 052 162
NISSAN	MATIC-W	VW	G 052 533
PORSCHE	LA 3403-M115	VW	G 052 990
PSA	P/N Z 000169756	VW	G 055 025
RENAULT	MATIC-D2	VW	G US 000 162
TOYOTA	TYPE T	ZF	TE-ML 11A
TOYOTA	TYPE T-III	ZF	TE-ML 11B

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm²/s	36.3
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.84
Viscosity index	ASTM D2270		150
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	218
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

