

WOLF AROW HV ISO 46

30/04/2026
4406

A high viscosity index paraffinic oil, based on selected ingredients, specifically intended for use in hydraulic circuits. Superior performance in keeping the system clean by reducing the formation of deposits. It also demonstrates good filterability, water separation, and quick air release.

APPLICATIONS

Hydraulic systems, functioning at very variable temperatures and at high pressures. Gear boxes, which require an oil with an increased viscosity index and assuring a mechanical and chemical stability. Regulation systems and hydraulic steering.

FEATURES

Anti-wear and oxidation stability: superior protection

Anti-foam properties: excellent anti-foam properties

Temperature stability: superior viscosity stability

SPECIFICATIONS

| | | | |
|-------|----------------|-------------------|-----------------------------|
| AFNOR | NF E 48-603 HV | PARKER (DENISON) | HF-0, HF-1, HF-2 |
| AFNOR | NF E 48-690 | SAE | MS1004 |
| AFNOR | NF E 48-691 | SEB | 181222 |
| AGMA | 9005-E02-RO | VICKERS | I-286-S3 |
| AIST | 126 (US Steel) | CINCINNATI | MACHINE P-70 (ISO 46) |
| AIST | 127 (US Steel) | DENISON | HF-0, HF-1, HF-2 |
| ASTM | D6158 HV | EATON VICKERS | I-286-S |
| DIN | 51524 Part 3 | EATON VICKERS | M-2950-S |
| ISO | 11158, HV | EATON | E-FDGN-TB002-E |
| ISO | 20763 | EATON | M-2950-S (35VQ25 pump test) |
| ISO | 6743-4, HV | GM | LS2 AW hyd.oil |
| JCMAS | HK P041 | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.876 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 46.0 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 8.1 |
| Viscosity index | ASTM D2270 | | 150 |
| Pour point | ASTM D6892 | °C | -39 |
| Flash Point COC | ASTM D92 | °C | 218 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

