

CHAMPION ALL-PURPOSE EP NR. 0

This is a semi-liquid Lithium grease. It has an excellent low temperature pumpability, maintaining its good flow property. By the use of "Extreme Pressure" additives, this grease is resistant to heavy shocks and loads. It has also excellent anti-corrosion, anti-rust and anti-oxidant-properties, which increase the life span of the grease and the lubricated parts.

APPLICATIONS

This grease can be used in both industrial and automotive applications. The consistency of the product makes it suitable for use in centralised lubrication systems that require semi-fluid grease. The product is also suitable for use in gearboxes. Temperature range: -30°C to +120°C, Max. +130°C

FEATURES

-: Easy to pump at low temperature

SPECIFICATIONS

DIN	51502	ISO	6743
DIN	KPOK-30	ISO	L-XCCFB0

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Texture	Visual		Smooth
Colour	VISUAL		Yellowish-Brown
NLGI Classification	ASTM D217		0
Worked Penetration [60 strokes]	ISO 2137	0.1 mm	370
Dropping point	ISO 2176/IP 396	°C	170
Four Ball Weld Load	ASTM D2596/ DIN51350:4	N	2600

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

