

WOLF SEMI-SYNT 2T

14/04/2025
1908

This is a semi synthetic lubricant based on carefully selected highly refined base oils, intended for the lubrication of 2-stroke gasoline engines with high specific power. This oil combines a high lubricity with a high thermal stability. Easily miscible with gasoline and efficient protection against deposits.

APPLICATIONS

This oil is specifically developed in order to satisfy the requirements of modern air cooled 2-stroke engines with a high specific power. Limited smoke formation.

FEATURES

Engine protection: excellent engine performance
Corrosion protection: adequate corrosion protection
Smoke suppression: smoke reduction

SPECIFICATIONS

API TC JASO FB
ISO L-EGB

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.882
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	78.4
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10.2
Viscosity index	ASTM D2270		112
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	1.1
Pour point	ASTM D6892	°C	-15
Sulfated Ash	ASTM D874	Mass %	0.28
Flash Point COC	ASTM D92	°C	100
Colour	VISUAL		AMBER

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

