

# COMPETE SN C2/C3 5W30

This full synthetic engine oil is designed to meet the core requirements of ACEA and API for passenger cars. It offers complete protection of both the aftertreatment system and the engine, regardless the driving conditions. This product may not be available in your region. Please, consult your local sales contact for more information.

## APPLICATIONS

Formulated to meet recent OEM specifications. It can be used to service a wide range of EURO 4 and EURO 5-engines of different manufacturers, with or without diesel particulate filter.

## FEATURES

- Broad coverage: reduced lubricant costs.
- Significant friction reduction: improved fuel efficiency and lowered emissions.

## PERFORMANCE PROFILE

### SPECIFICATIONS

ACEA - C2

ACEA - C3

API - SN/CF

MB - 229.31

## TYPICAL CHARACTERISTICS

TEST	METHOD	UNIT	AVERAGE RESULTS
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	68.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	11.8
Viscosity index	ASTM D2270		171
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	6.8
Pour point	ASTM D6892	°C	-39
Sulfated Ash	ASTM D874	Mass %	0.78
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.