

# CHAMPION OEM LEVEL 5W30 LL III

This full synthetic engine oil is formulated to meet the specifications of different OEMs. It reaches ACEA and API requirements by balancing excellent fluidity with advanced engine protecting, regardless the driving conditions. This product may not be available in your region. Please, consult your local sales contact for more information.

## APPLICATIONS

Its formulation is designed to meet the VW 504.00 and 507.00 specifications. This engine oil can be used to service a range of different EURO 4 and EURO 5-engines equipped with diesel particulate filters.

## FEATURES

Aftertreatment protection:: full aftertreatment device protection.

Total engine protection:: outstanding engine cleanliness and durability.

## SPECIFICATIONS

<b>ACEA</b>	C2	<b>MB</b>	229.52
<b>ACEA</b>	C3	<b>OPEL</b>	GM-LL-A-025
<b>API</b>	approval SN	<b>OPEL</b>	GM-LL-B-025
<b>API</b>	CF	<b>OPEL</b>	OV 040 1547 - D30
<b>BMW</b>	LONGLIFE-04	<b>PORSCHE</b>	C30
<b>FIAT</b>	9.55535-S3	<b>VW</b>	503 01
<b>MB</b>	229.31	<b>VW</b>	504 00/507 00
<b>MB</b>	229.51		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	68.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	11.7
Viscosity index	ASTM D2270		169
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	8.3
Pour point	ASTM D6892	°C	-39
Sulfated Ash	ASTM D874	Mass %	0.7
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

