

WOLF TRACTOFLUID 170 A

03/04/2026
23114

Semi-synthetic UTTO oil, intended for automatic transmissions, CVT, hydraulic systems, wet brakes, converters for tractors, forklifts, and different off-highway equipment. Remark : When the manufacturer prescribes only one oil for the lubrication of all parts, the engine included, he refers to a S.T.O.U. oil.

APPLICATIONS

Specifically developed for agricultural equipment of Fendt.

This oil can be used in transmissions, lifters, rear axles and wet brakes of agricultural tractors and off-highway equipment as well as moving hydraulic systems (cranes, junctions, power steering).

FEATURES

Anti-wear and oxidation stability: superior protection of critical parts

Cold start: excellent fluidity at low temperature

SPECIFICATIONS

API	GL-4	FORD	ESN-M2C-134 C/D
ASTM	D6973 (EATON 35VQ) PUMP TEST	FORD	ESN-M2C-86 A/B
DIN	51524 Part 2	FORD	ESN-M2C-86 C
AGCO/ALLIS	821 XL	FORD	FNHA-2-C-201.00
AGCO/ALLIS	Q-186 (White Farm)	FORD	M2C-48 C3
ALLISON	C4	GIMA	SFU
CASE	MAT 3505	JCB	GOHP PLUS
CASE	MAT 3506	JCB	Standard 4000/2200
CASE	MAT 3509	JD	J20 C/D
CASE	MAT 3510	KOMATSU	AXO 80
CASE	MAT 3525	KOMATSU	KES 07.866
CASE	MAT 3526	KUBOTA	UDT
CASE	MAT 3540	MF	M 1127/M 1129A
CASE	MAT 3552A	MF	M 1135
CASE	MS1204	MF	M 1141
CASE	MS1205	MF	M 1143
CASE	MS1206	MF	M 1145
CASE	MS1207	NH	NH 410B
CASE	MS1209	NH	NH 410C
CASE	MS1210	NH	NH 82948718
CASE	MS1230	SDFG	OT-1891
CATERPILLAR	MTO	SDFG	OT-1891A
CATERPILLAR	TO-2	VALTRA	G2-08
CHRYSLER	MS 10216	VALTRA	G2-B10
CLAAS	RENAULT AGRICULTURE M 1145	VOLVO	97303/WB101
DENISON	HF-0, HF-1, HF-2	ZF	TE-ML 03E
DENISON	UTTO/THF	ZF	TE-ML 05F
FENDT	FWN 81001	ZF	TE-ML 06B

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



ZF	TE-ML 06D	ZF	TE-ML 06N
ZF	TE-ML 06E	ZF	TE-ML 06P
ZF	TE-ML 06F	ZF	TE-ML 06R
ZF	TE-ML 06H	ZF	TE-ML 06S
ZF	TE-ML 06K	ZF	TE-ML 06T
ZF	TE-ML 06L	ZF	TE-ML 17E
ZF	TE-ML 06M	ZF	TE-ML 21F

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.857
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	68.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.4
Viscosity index	ASTM D2270		162
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	8.6
Pour point	ASTM D6892	°C	-36
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

