

WOLF EXTENDTECH

80W-90 GL 5

28/10/2025
2308

This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

APPLICATIONS

Recommended for all hypoid transmissions and also suitable for spiral bevel gears, worm wheels and most transaxles.

FEATURES

Frictional properties: easy gear shifting
Anti-wear protection: long transmission life

SPECIFICATIONS

API	GL-5	ZF	TE-ML 12E
MIL	L-2105 C	ZF	TE-ML 16B
MIL	L-2105 D	ZF	TE-ML 16C
MAN	342 M-1	ZF	TE-ML 17B
MAN	342 M-2	ZF	TE-ML 19B
ZF	TE-ML 05A	ZF	TE-ML 21A
ZF	TE-ML 07A		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.8970
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	148.62
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	15.20
Viscosity index	ASTM D2270		103
Pour point	ASTM D6892	°C	-33
Brookfield viscosity at -26 C	ASTM D2983	mPa.s	120000
Flash Point COC	ASTM D92	°C	210

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.