

# WOLF RADIATOR SEALER & CONDITIONER

14/04/2025  
70316

This product seals and permanently prevents hair cracks and leakages in the radiator, the water pump, the cylinder head gasket and the engine block. It protects the entire cooling system against rust and corrosion and lubricates the water pump. It does not harm rubber hoses, metal parts and gaskets.

## APPLICATIONS

Suitable for all aluminium, plastic and steel radiators of cooling systems in petrol, diesel and LPG engines. Compatible with water, cooling fluids and conventional anti freeze. Directions for use: Shake well before use and pour the content of the can into the cooling system with switched-on heating and warm (not hot) running engine. Keep engine running for approximately 10 minutes or drive a short distance. Be careful when opening the radiator/cooling system as hot coolant or steam might escape from the system. Dirty cooling systems should first be cleaned with Radiator Cleaner. The amount of 325ml is sufficient for cooling systems with a volume of up to 12 litres.

## FEATURES

Sealing and conditioning: complete cooling system protection Protecting the entire cooling system against rust and corrosion Lubricating the water pump

## SPECIFICATIONS

/ /

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	1.026
Colour	VISUAL		BROWN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

