

CHAMPION RADIATOR CLEANER

This product has been developed to clean the entire cooling system and to improve the heat transfer from the engine to the cooling system. It removes sludge, rust, scale and other deposits. Prevents overheating, build up of acids and contaminants.

APPLICATIONS

Suitable for all aluminium, plastic and steel radiators of cooling systems in petrol, diesel and LPG engines. Compatible with water, cooling fluids and conventional anti-freeze. Directions for use: Shake well before use and pour the contents of one bottle into the radiator. Drive for about 30 minutes and drain the cooling system. Flush with water and refill the cooling system. Be careful when opening or draining the radiator/cooling system as hot steam or coolant might escape. One 325ml bottle is sufficient for cooling systems of up to 12 liters.

FEATURES

Cleaning action: complete removal of all deposits

SPECIFICATIONS

/ /

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
pH	ASTM D1287		10.0
Density at 20°C	ASTM D4052	g/ml	1.000
Colour	VISUAL		NEUTRAL-SHAZY

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

