

CHAMPION **ECO FLOW** DSG FLUID

This is a full synthetic lubricant based on carefully selected very high quality base oils, specifically developed for the dual clutch transmissions (DCT) of modern passenger cars. It ensures trouble-free operation of these gearboxes.

APPLICATIONS

Mainly intended for the DSG (Direct Shift Gearbox) of VAG, this fluid can also be used for other 6-speed DCT transmissions, such as Chrysler Powershift, Ford Powershift, Mitsubishi TC-SST, Volvo Powershift, BMW Drivelogic 7-speed, etc.

FEATURES

Anti-wear protection: significantly extended transmission life

Frictional properties: very smooth gear shifting, no vibration

Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

API	GL-4	FORD	WSS-M2C200-D3
BENTLEY	G 052 524-B2	FORD	WSS-M2C200-E1
BMW	83220306816	FORD	WSS-M2C218-A1
BMW	83220397244	FORD	WSS-M2C936-A
BMW	83220440214	GM	DEXRON DCT
BMW	83222147477	GM	FFL-4
BMW	83222148578	GREAT WALL	GW7DCT1
BMW	83222148579	GREAT WALL	GWM 7DCT450
BMW	83222167666	HONDA	MTF III
BMW	83222409710	HYUNDAI	04300-2N110 WDHO-1
BMW	83222433157	KIA	04300-2N110 WDHO-1
BMW	83225B3AC81	KUNLUN	DCTF-7S
BMW	DCTF-1	MB	236.21
BMW	DCTF-2	MB	236.22
BMW	DTF 1	MB	236.24
BMW	FFL-4	MB	236.25
BMW	MTF LT-3	MB	239.21
BMW	MTF LT-5	MB	239.22
CHERY	730DHB/DHC 7DCT300	MB	SLS A0019898603
CHERY	738DHA 7DCT380	MCLAREN	FFL-4
CHERY	9009011085	MITSUBISHI	DIAMOND QUEEN SSTF-1
CHRYSLER	68044345EA	NISSAN	999MP-6TRT00P
DTFR	13C130	NISSAN	DCT FLUID
FERRARI	TF DCT-F3	NISSAN	GR6
FIAT	9.55550-DA11	NISSAN	GT-R R35
FIAT	9.55550-HE2	NISSAN	LV MTF-1
FIAT	9.55550-MZ2	NISSAN	R35 SPECIAL
FIAT	9.55550-MZ6	PORSCHE	000.043.20
FORD	F-DC	PORSCHE	000.043.207.29
FORD	WSS-M2C200-D2	PORSCHE	000.043.207.30

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION
LUBRICANTS

PORSCHE	000.043.210.44	VOLVO	1161839
PORSCHE	000.043.305.63	VOLVO	32240415
PORSCHE	971.094.307.02A	VOLVO	32240419
PORSCHE	999.917.080.00	VOLVO	B0T341 #1161838
PORSCHE	999.917.080.01	VOLVO	D1
PORSCHE	999.917.546.00	VOLVO	D2
PORSCHE	TF 0870	VW	G 052 171
PSA	1618078480	VW	G 052 178
PSA	9730 A8	VW	G 052 182
PSA	9734 S2	VW	G 052 512
PSA	JWS 2271	VW	G 052 513
PUNCH	DT2	VW	G 052 524
RENAULT	7711579456	VW	G 052 527
RENAULT	7711785243	VW	G 052 529
RENAULT	B0T450 EDC 6-Speed	VW	G 052 726
RENAULT	DC4	VW	G 052 798
RENAULT	DW5	VW	G 055 512
RENAULT	DW6	VW	G 055 524
SINOPEC	DCTF-GS	VW	G 055 529
STELLANTIS	16 934 837 80	VW	G 055 549
SUZUKI	99000-22B27-036	VW	G 060 726
TOYOTA	0888581001	VW	G 070 726
TOYOTA	JWS 2271	VW	G009317
TOYOTA	LF	VW	TL 521 82
TOYOTA	LV 75W MT	ZF	0671090545
VOLVO	1161520-7		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm²/s	33.6
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.87
Viscosity index	ASTM D2270		170
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	11000
Flash Point COC	ASTM D92	°C	198

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

