

# CHAMPION COMPETE

## CI-4/SL 15W40

*This engine oil meets the prime requirements of ACEA and API for heavy-duty engines. It combines wear reducing- and cleaning properties into one lubricant.*

### APPLICATIONS

*Suitable for all modern Euro II, III and some Euro IV diesel engines of heavy-duty equipment, making it a great lubricant for mixed fleet maintenance.*

### FEATURES

*Engine protection: outstanding engine cleanliness and durability*

### SPECIFICATIONS

<b>ACEA</b>	A3/B4	<b>API</b>	CG-4
<b>ACEA</b>	E7	<b>API</b>	CH-4
<b>API</b>	approval CI-4/SL	<b>MB</b>	229.1

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.882
Kinematic viscosity at 40°C	ASTM D445	mm²/s	95.7
Kinematic viscosity at 100°C	ASTM D445	mm²/s	13.7
Viscosity index	ASTM D2270		145
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	8
Pour point	ASTM D6892	°C	-33
Flash Point COC	ASTM D92	°C	225

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

