

CHAMPION OUTBOARD

2T TC-W3 DFI

This is a semi synthetic oil for water-cooled 2-stroke outboard engines, meeting the NMMA-specification TC-W3. Its ashless composition prevents the formation of deposit, pre-ignition and spark plug fouling. High protection against rust and corrosion.

APPLICATIONS

All water-cooled 2-stroke gasoline engines with high power, such as outboard motors, jet skis and personal watercraft. Dilution according to the manufacturer's instructions.

FEATURES

Engine protection: outstanding engine cleanliness and durability

Corrosion protection: adequate corrosion protection

SPECIFICATIONS

API	TC	NMMA	TC-W3
JASO	FC		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.859
Kinematic viscosity at 40°C	ASTM D445	mm²/s	42.7
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.8
Viscosity index	ASTM D2270		155
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	5.2
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	0
Flash Point COC	ASTM D92	°C	100
Colour	VISUAL		BLUE

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

