

WOLF ESSENTIAL

CI-4/SL 15W40

06/07/2026
75702

This engine oil meets the prime requirements of ACEA and API for heavy-duty engines. It combines wear reducing- and cleaning properties into one lubricant.

APPLICATIONS

Suitable for all modern Euro II, III and some Euro IV diesel engines of heavy-duty equipment, making it a great lubricant for mixed fleet maintenance.

FEATURES

Engine protection: outstanding engine cleanliness and durability

SPECIFICATIONS

ACEA	A3/B4	API	CH-4
ACEA	E7	DTFR	15B110
API	approval CI-4/SL	MB	229.1
API	CG-4		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.882
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	95.7
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.7
Viscosity index	ASTM D2270		145
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	10.9
Pour point	ASTM D6892	°C	-33
Flash Point COC	ASTM D92	°C	225

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

